


WR0<5 QSQ Silicon NPN transistor in a TO-92 Plastic Package.

f_w / 5VD434;+D,
 High V_{CEO} , high f_T , Complementary pair with 2SA1018(A).


General amplifier applications.



PIN1 Base PIN 2 Collector PIN 3 Emitter


h_{FE} Classifications Symbol	P	Q	R
h_{FE} Range	30~100	60~150	100~220

Parameter	Symbol		Rating	Unit
Collector to Base Voltage	V_{CBO}	2SC1473	250	V
		2SC1473A	300	
Collector to Emitter Voltage	V_{CEO}	2SC1473	200	V
		2SC1473A	300	



EU:
F47 : 6D
S: h_{IH}

Note:
BR: Company Code.
C1473A: Product Type.
P: h_{FE} Classifications Symbol
****: Lot No. Code,code change with Lot No.



Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 , Time:60~90sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

270±5

10±1 sec.

Temp:270±5

Time:10±1 sec

/ BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195
	1,000	10	10,000	10	100,000	135×190	237×172×102	560×245×375

/ AMMO

Package Type	Units					Dimension (unit mm3)	
	Units/tape /	Tape/Inner Box /	Rows/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Inner Box	Outer Box
TO-92	3,000	1	120	10	30,000	328×230×42	480×346×235 547×407×268