

TO-92 NPN Silicon NPN transistor in a TO-92 Plastic Package.

h_{FE}

High breakdown voltage, excellent linearity of h_{FE} and small C_{ob} , fast switching speed.





60

High voltage switching. AF 60W pre-driver applications.



PIN1 Base PIN 2


/ Electrical Characteristic Curve




/ PackageDimensions

TO-92

Unit: mm



/ Marking Instructions



BR:

C2909

R: h_{FE}

Note:


BR: Company Code.

C2909: Product Type.

R: h_{FE} Classifications Symbol.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5	10±1 sec.	Temp:270±5	Time:10±1 sec
-------	-----------	------------	---------------

/ Packaging SPEC.

/ BULK

Package Type	Units	Dimension	(unit mm3)
--------------	-------	-----------	------------