

**/ Descriptions**

Silicon NPN transistor in a TO-126F Plastic Package.


**/ Features**

High voltage, small collector output, capacitance.

**/ Applications**

High voltage switching and amplifier applications, color TV chroma output applications and, color TV horizontal driver.

**/ Equivalent Circuit**



**/ Pinning**



PIN1 Emitter      PIN 2 Collector      PIN 3 Base

**/  $h_{FE}$  Classifications & Marking**

See Marking Instructions.


**/ Absolute Maximum Ratings(Ta=25 )**

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	300	V
Collector to Emitter Voltage	$V_{CEO}$	300	V
Emitter to Base Voltage	$V_{EBO}$	7.0	V
Collector Current - Continuous	$I_C$	100	mA
Base Current- Continuous	$I_B$	50	mA
Collector Power Dissipation	$P_C$	1.3	W
Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 150	

**/ Electrical Characteristics(Ta=25 )**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cut-Off Current	$I_{CBO}$	$V_{CB}=240V$ $I_E=0$			1.0	$\mu A$
Emitter Cut-Off Current	$I_{EBO}$	$V_{EB}=7.0V$ $I_C=0$			1.0	$\mu A$
DC Current Gain	$h_{FE(1)}$	$V_{CE}=10V$ $I_C=20mA$	30		200	
	$h_{FE(2)}$	$V_{CE}=10V$ $I_C=4.0mA$	20			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=10mA$ $I_B=1.0mA$			1.0	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=10mA$ $I_B=1.0mA$			1.0	V
Transition Frequency	$f_T$	$V_{CE}=10V$ $I_C=20mA$	50	70		MHz
Collector output capacitance	$C_{ob}$	$V_{CB}=20V$ $f=1.0MHz$ $I_E=0$		3.0		pF



/ Electrical Characteristic Curve




/ Package Dimensions

IP-126F

单位: mm



/ Marking Instructions




Note:

BR: Company Code

C5027: Product Type.

\*\*\*\*: Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



Note:

1            25   150