

/ Descriptions

PDFN3×3A-8L N MOS

N-Channel Enhancement Mode Field Effect Transistor in a PDFN3×3A-8L Plastic Package.



/ Features $V_{DS} (V) = 30V$ $I_D = 30 A (V_{GS} = \pm 20V)$ $R_{DS(ON)} @ 10V \leq 9mR (Typ. 8mR)$

HF Product.

/ Applications

DC/DC

These devices are well suited for high efficiency switching DC/DC converters and switch mode power supplies.

/ Equivalent Circuit**/ Pinning**

出脚	定义
Pin1	S
Pin2	C
3	D
4	S
5	C
6	D
7	S
8	C

/ Marking

See Marking Instructions.

BRCS080N03YB

Rev.B Oct.-2024

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V$ $V_{GS}=0V$			1	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 0.1	μA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	1.0	1.9	2.5	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=20A$		8	9	$m\Omega$
		$V_{GS}=4.5V$ $I_D=10A$		12	15	$m\Omega$
Drain-Source Diode Forward Voltage	V_{SD}	V				



BRCS080N03YB

Rev.B Oct.-2024



DATA SHEET


/ Electrical Characteristic Curve



/ Package Dimensions


PDFN3X3A-8L

Unit:mm



Rev.00 202011

/ Marking Instructions



BR

080N03

Note:

BR: Company Code

080N03: Product Type Code

****: Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension		(unit mm ³)
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	