



Rev.A May.-2022

$G; =E * 2 * \$ / C$ $E \quad ' D F J$
 ; f l Y Δ ' E \$? 8 E E < C' D F J = < K ` e X' G; =E * 2 * \\$ / C G α j k Z ' G X Z b X ^ \ %

$V_{DS} (V) = 30V$
 $I_D = 24A (V_{GS} = \pm 20V)$
 $R_{DS(ON)} @ 10V \quad 13mR (Typ. 11mR)$
 ? = G i f [| Z K %



@ k \ e [\ [] f i l j \ ` e ` ^ \ e \ i X c g l i g f j \ j n ` k Z _ e ^ ` X e [' g _ X j \ ` Z f e k f c X g g c Z X k f e j %




See Marking Instructions.

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	30	V
Drain Current		$I_D(T_C=25^\circ\text{C})$	24	A
Drain Current - Pulsed		I_{DM}	55	A
Gate-Source Voltage		V_{GSS}	± 20	V
Single Pulsed Avalanche Energy		E_{AS}	199	mJ
Avalanche Current		I_{AS}	12.9	A
Power Dissipation		$P_D(T_C=25^\circ\text{C})$	15.5	W
Operating and Storage Temperature Range		T_J, T_{stg}	-55 to 150	
Junction-to-Ambient	$t = 10$	R_{JA}	40	/W
Junction-to-Ambient	Steady-State		75	
Junction-to-Case	Steady-State	R_{JC}	9	

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$	$I_D=250 A$	30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V$	$V_{GS}=0V$			1	A
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$	$V_{DS}=0V$			± 0.1	A
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$	$I_D=250 A$	1.0	1.8	3.0	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$	$I_D=20A$		11	13	m
		$V_{GS}=4.5V$	$I_D=10A$		16	20	m
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$	$I_S=1A$			1.2	V
Input Capacitance	C_{iss}	$V_{DS}=25V$ $f=1.0MHz$	$V_{GS}=0V$		666		pF
Output Capacitance	C_{oss}				26		
Reverse Transfer Capacitance	C_{rss}				63		
Gate resistance	R_g	$V_{GS}=0V$ $f=1MHz$	$V_{DS}=0V$		1.7		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$ $I_D=8A$	$V_{DS}=15V$		13.6		nC
Total Gate Charge	$Q_{g(4.5V)}$				6.8		
Gate Source Charge	Q_{gs}				1.6		
Gate Drain Charge	Q_{gd}				3.6		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $R_L=1.87$	$V_{DS}=15V$ $R_{GEN}=4.5$		5		ns
Turn-On Rise Time	t_r				3.5		
Turn-Off Delay Time	$t_{d(off)}$				22		
Turn-Off Fall Time	t_f				4.5		







Rev.A May.-2022

PDFN3X3-8L

Unit:mm





BR

120N03

!!!!

Note:

BR: Company Code

120N03: Product Type Code

****: Lot No. Code, code change with Lot No

Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- | | | | |
|---|-----------|-------------|---|
| 1 | 150 ~ 180 | 60 ~ 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245..5 | 5..0.5sec; | 2.Peak Temp.:245..5 , Duration:5..0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

260..5	10..1 sec.	Temp.:260..5	Time:10..1 sec
--------	------------	--------------	----------------

/ REEL

Package Type	Units	Dimension	(unit mm ³)
--------------	-------	-----------	-------------------------