

Rev. D Oct.-2018

SOP-8 N MOS

N-Channel Enhancement Mode Field Effect Transistor in a SOP-8 Plastic Package.



$V_{DS}(V)=30V$ $I_D=6.9A$

$R_{DS(ON)} < 32m\Omega (V_{GS}=10V)$

$R_{DS(ON)} < 36m\Omega (V_{GS}=4.5V)$

$R_{DS(ON)} < 52m\Omega (V_{GS}=2.5V)$

Power Management in Notebook computer, Portable Equipment and Battery powered systems and this device is suitable for use as a load switch or in PWM applications.



PIN1	S2	PIN 2	G2	PIN 3	S1	PIN 4	G1
PIN 5	D1	PIN 6	D1	PIN 7	D2	PIN 8	D2

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ^A	$I_D (T_a=25^\circ\text{C})$	6.9	A
	$I_D (T_a=70^\circ\text{C})$	5.8	A
Pulsed Drain Current ^B	I_{DM}	40	A
Power Dissipation for Single Operation ^A	$P_D (T_a=25^\circ\text{C})$	2.0	W
	$P_D (T_a=70^\circ\text{C})$	1.44	W
Junction and Storage Temperature Range	T_j, T_{stg}	-55 +150	
Thermal Resistance-Junction to Ambient ^A	$R_{\theta JA} \quad t \leq 10s$	62.5	/W
	$R_{\theta JA}$	110	/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	40	/W

Note:

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any a given application depends on the user's specific board design. The current rating is based on the $t \leq 10s$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.


D. The static characteristics in Figures 1 to 6 are obtained using 80 μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

Rev. D Oct.-2018





Rev. D Oct.-2018




Rev. D Oct.-2018

/







BR

4800


Note:

BR: Company Code.

4800: Product Type

****: Lot No. Code, code change with Lot No.

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

2

245±5

5±0.5sec;

3

2 10 /sec.
- 1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension		(unit mm ³)