







f

Parameter	Symbol	Rating	Unit
Output Voltage	$V_{CC}$	50	V
Input Voltage	$V_{IN}$	40	V
		-10	V
Output Current	$I_{CM}$	100	mA
	$I_O$	50	mA
Collector Dissipation	$P_C$	200	mW
Junction Temperature	$T_j$	150	°C
Storage Temperature Range			





# H211<sup>\*\*</sup>

\*

● " 1"

H211

\*\*\*:

Note:

● "1" Pin

H211 Product Type Code

\*\*\*: Lot No. Code, code change with Lot No.



= @ " " "


Note:

- |   |         |           |   |
|---|---------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec.   |
| 2 | 245 5   | 5 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | 2 10    | /sec.     | 3. Cooling Speed: 2~10 /sec.            |

#&#203)#\*fi \*' #(%36iž #02iž#&2fi . \* 3 '%2% \* 3&fi

260 5                      10 1 sec.                      Temp.:260±5°C                      Time:10±1 sec

fi "fi fi C0)506%36fi fi C! . Efi

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm <sup>3</sup> )		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-363	3,000	10	30,000	6	18,000	7" x8	180x120x180	390x385x205