

/ Descriptions

WR0553I SQS Silicon PNP transistor in a TO-220F Plastic Package.


/ Features

WLS455I
Complement to TIP122F.


/ Applications

Medium power linear switching applications.

/ Equivalent Circuit



/ Pinning






PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	100	V

/ Electrical Characteristic Curve



/ Marking Instructions



EU

WLS45 : I


Note:

BR: Company Code.

TIP127F: Product Type Code.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|------|----|----------|---|
| 1 | 25 | 150% | 60 | 90sec; | 1.Preheating:25~150%, Time:60~90sec. |
| 2 | 255 | ±5% | 5 | ±0.5sec; | 2.Peak Temp.:255 ±5%, Duration:5 ±0.5sec. |
| 3 | | | 2 | 10%/sec. | 3. Cooling Speed: 2~10%/sec. |

/ Resistance to Soldering Heat Test Conditions

270 ±5% 10 ±1 sec. Temp:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type	Units	Dimension (unit mm3)
--------------	-------	----------------------